



Vardaflex Wallpaper Backlite-V2


Flex.LED-Flächenplatine, 24V, 36W, Innen, 2700K CRI90

Article nr.: PCF007

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 48 mm / 1 LEDs teilbar · Anzahl der LEDs: 50 · LED Abstand: 48 mm · min. Biegedurchmesser: 20 mm · Ausstrahlwinkel: 160° · CRI: >90 · Lichtstrom: 2634 lm · Betriebsspannung: 24V DC · Leistung: 36 W · Leistung pro LED: 0,72 W · Lebensdauer L70: >= 50.000 h · LxBxH in mm: 480 x 240 x 6,5 · · Maximale Anzahl pro Anschluss: 6 x VARDaflex Wallpaper · Lieferumfang: 1x flexible Leiterplatte, 2x Einspeisungsverbinder, · 2x Flexverbinder

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835830072
Housing colour	Weiss
Length	480.00 mm
Width	240.00 mm
Height	6.50 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	2634.00 lm
Lightoutput per LED	52.68 lm
Lamp	Inklusive LED





Vardaflex Wallpaper Backlite-V2
Flex.LED-Flächenplatine, 24V, 36W,
Innen, 2700K CRI90
Article nr.: PCF007

TECHNICAL DATA

IP rating	20
Power	36 W
Current mA	1500 mA
Voltage	24 V
Amount of LED	50
Temperature range	-20 - 60
Dimension of segments	48.00 mm
CRI	≥ 90





Vardaflex Wallpaper Backlite-V2

Flex.LED-Flächenplatine, 24V, 36W,
Innen, 2700K CRI90

Article nr.: PCF007

TECHNICAL DRAWING

