




CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 4000K, CRI90, D80mm-40°

Article nr.: PEG121

LED Power Modul 31 W mit Reflektor · mit Luminus-CXM-14 Power LED Array Gen. 4 · für Einbaustrahler der CORU-80(K) Produktfamilie · · Betriebsstrom: 900 mA DC · Leistung: 31 W · Lichtstrom: 3.498 lm · Lichtfarbe: 4000 K · CRI: >90 · Lebensdauer L70 >= 50.000 h · Ausstrahlwinkel: 40° · Schutzklasse III · · Sehr gute Wärmeableitung durch optimierten Aluminium-Kühlkörper · Aluminiumreflektor mit Halogenoptik und gleichmäßiger Lichtverteilung · Mit 500 mm Anschlussleitung und JST-Steckverbindung zum verpolungssicheren · und werkzeuglosen Tausch des Leuchtmittels · inklusive Konstantstrom-Konverter schaltbar · Eingangsspannung: 220-240 V AC 50/60 Hz · Schutzklasse II

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835851213
Housing colour	Grau
Height	103.00 mm
Outer diameter	85 mm
Hole size	80 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	3498.00 lm
Lamp	Inklusive LED
IP rating	40







CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 4000K, CRI90, D80mm-40°
Article nr.: PEG121

TECHNICAL DATA

Power	31 W
Current mA	900 mA
Voltage	220-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 35
CRI	≥ 90
Lifetime L70B50	50.000 h





CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 4000K, CRI90, D80mm-40°
Article nr.: PEG121

TECHNICAL DRAWING

