




VARDaflex Plus Profi DTW - 5-Meter- Rolle Flex. LED-Strip, 24V, 13W/m, Innen, DTW CRI80

Article nr.: PGI040

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 100 mm / 14 LEDs teilbar ·
Anzahl der LEDs: 700 · LED Abstand: 14,29 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro
Meter: 1317 lm · Lichtfarbe: 3000 K - 1900 K (Dim To Warm) · Betriebsspannung: 24 V DC · Leistung
pro Meter: 13 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000
x 10 x 1,4 · · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. ·
Lieferumfang: 5 Meter-Rolle

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835890403
Housing colour	sonstige
Length	5000.00 mm
Width	10.00 mm
Height	1.40 mm
LED colour	3000-1900K Dim to Warm
Lightoutput per fixture	6585.00 lm
Lightoutput per LED	9.41 lm
Lamp	Inklusive LED






VARDAflex Plus Profi DTW - 5-Meter- Rolle Flex. LED-Strip, 24V, 13W/m, Innen, DTW CRI80

Article nr.: PGI040

TECHNICAL DATA

IP rating	20
Power	65 W
Psb	0,00 W
Current mA	2708 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h





**VARDAflex Plus Profi DTW - 5-Meter-
Rolle Flex. LED-Strip, 24V, 13W/m,
Innen, DTW CRI80**
Article nr.: PGI040

TECHNICAL DRAWING

