



VARDAflex Double 5 M- R.


Flex.LEDStrip, 24V, 19, 2W/m, 3700-4200K-Seafood

Article nr.: PGI122

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 33,33 mm / 7 LEDs teilbar ·
Anzahl der LEDs: 1050 · LED Abstand: 4,76 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro
Meter: 2313 lm · Betriebsspannung: 24 V DC · Leistung pro Meter: 19,2 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 8 x 1,5 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835891226
Length	5000.00 mm
Width	8.00 mm
Height	1.50 mm
LED colour	ca. 4000K seafood
Lightoutput per fixture	11565.00 lm
Lightoutput per LED	11.01 lm
Lamp	Inklusive LED
IP rating	20






VARDAflex Double 5 M- R.

Flex.LEDStrip, 24V, 19, 2W/m, 3700-4200K-Seafood

Article nr.: PGI122

TECHNICAL DATA

Power	96 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	1050
Temperature range	-20 - 45
LED per meter	210
Dimension of segments	33.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h





VARDAflex Double 5 M- R.

Flex.LEDStrip, 24V, 19, 2W/m, 3700-
4200K-Seafood

Article nr.: PGI122

TECHNICAL DRAWING

