



LED-Strip VARDaflex Superior Photon


High CRI, IP20 24V, 23W/m, 940+, 5m

Article nr.: PGI298

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 62,5 mm / 8 LEDs teilbar · anzahl der LEDs: 640 · LED Abstand: 7,81 mm · Ausstrahlwinkel: 120° · CRI: 98 · Lichtstrom pro Meter: 3027 lm · Eingangsspannung: 24 V DC · Leistung pro Meter: 23 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 12 x 1,6 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter Rolle

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835892988
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	1.60 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	15135.00 lm
Lightoutput per LED	23.65 lm
Lamp	Inklusive LED





LED-Strip VARDaFlex Superior Photon
High CRI, IP20 24V, 23W/m, 940+, 5m
Article nr.: PGI298

TECHNICAL DATA

IP rating	20
Power	115 W
Psb	0,00 W
Current mA	4792 mA
Voltage	24 V
Amount of LED	640
Temperature range	-20 - 45
LED per meter	128
Dimension of segments	62.50 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 98
Lifetime L70B50	50.000 h





LED-Strip VARDaFlex Superior Photon
High CRI, IP20 24V, 23W/m, 940+, 5m
Article nr.: PGI298

TECHNICAL DRAWING

