



VARDAflex Eco-7 Plus - 5-Meter-Rolle


Flex. LED-Strip, 24V, 9, 6W/m, Innen, 3000K CRI90

Article nr.: PGI435

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 50 mm / 7 LEDs teilbar · Anzahl der LEDs: 700 · LED Abstand: 7,14 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 965 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 9,6 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000 x 8 x 1,5 · · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835894357
Length	5000.00 mm
Width	8.00 mm
Height	1.50 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4825.00 lm
Lightoutput per LED	6.89 lm
Lamp	Inklusive LED
IP rating	20






VARDAflex Eco-7 Plus - 5-Meter-Rolle

Flex. LED-Strip, 24V, 9, 6W/m, Innen, 3000K CRI90

Article nr.: PGI435

TECHNICAL DATA

Power	48 W
Psb	0,00 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h





VARDAflex Eco-7 Plus - 5-Meter-Rolle
Flex. LED-Strip, 24V, 9, 6W/m, Innen,
3000K CRI90
Article nr.: PGI435

TECHNICAL DRAWING

