




LED-Strip VARDaflex 90-7 Double, IP20 24V, 19, 2W/m, 930, 5m

Article nr.: PGI465

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 33,33 mm / 7 LEDs teilbar · Anzahl der LEDs: 1.050 · LED Abstand: 4,76 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 1.667 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 19,2 W · Lebensdauer L70: >= 50.000 h · LxBxH in mm: 5.000 x 8 x 1,5 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835894654
Length	5000.00 mm
Width	8.00 mm
Height	1.50 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	8335.00 lm
Lightoutput per LED	7.94 lm
Lamp	Inklusive LED
IP rating	20






LED-Strip VARDaFlex 90-7 Double, IP20 24V, 19, 2W/m, 930, 5m

Article nr.: PGI465

TECHNICAL DATA

Power	96 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	1050
Temperature range	-20 - 45
LED per meter	210
Dimension of segments	33.33 mm
CRI	≥ 90
Lifetime L70B50	50.000 h





LED-Strip VARDAflex 90-7 Double, IP20
24V, 19, 2W/m, 930, 5m
Article nr.: PGI465

TECHNICAL DRAWING

