



## VARDAflex Quantum - 5-Meter-Rolle


### Flex. LED-Strip, 24V, 6, 5W/m, Innen, 2700K CRI80

Article nr.: PHD347

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 125 mm / 8 LEDs teilbar ·  
Anzahl der LEDs: 320 · LED Abstand: 15,63 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro  
Meter: 969 lm · Betriebsspannung: 24 V DC · Leistung pro Meter: 6,5 W · Lebensdauer L70B50: >=  
60.000 h · Lebensdauer L80: >= 83.000 h · Energieeffizienzklasse: D · LxBxH in mm: 5.000 x 10 x 1,3 · ·  
Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5  
Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle, 5 x Einspeisungsverbinder  
Profi, · 1 x Direktverbinder Profi · Förderfähig nach BEG Förderprogramm 2021 - 2030

#### TECHNICAL DATA

|                         |                          |
|-------------------------|--------------------------|
| Unit Code               | Stück                    |
| BAR code                | 4251835843478            |
| Housing colour          | Weiss                    |
| Length                  | 5000.00 mm               |
| Width                   | 10.00 mm                 |
| Height                  | 1.30 mm                  |
| LED colour              | ca. 2700K ultra warmweiß |
| Lightoutput per fixture | 4845.00 lm               |
| Lightoutput per LED     | 15.14 lm                 |
| Lamp                    | Inklusive LED            |





## VARDAflex Quantum - 5-Meter-Rolle

### Flex. LED-Strip, 24V, 6, 5W/m, Innen, 2700K CRI80

Article nr.: PHD347

#### TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 20          |
| Power                   | 32,5 W      |
| Psb                     | 0,00 W      |
| Current mA              | 1354 mA     |
| Voltage                 | 24 V        |
| Amount of LED           | 320         |
| Temperature range       | -20 - 45    |
| LED per meter           | 64          |
| Dimension of segments   | 125.00 mm   |
| Energy efficiency class | EEK-Label_D |
| CRI                     | ≥ 80        |
| Lifetime L70B50         | 60.000 h    |





**VARDaflex Quantum - 5-Meter-Rolle**  
**Flex. LED-Strip, 24V, 6, 5W/m, Innen,**  
**2700K CRI80**

Article nr.: PHD347

**TECHNICAL DRAWING**

