



VARDAflex Outdoor - 30-Meter-Rolle


Flex. LED-Strip, 24V, 6W/m, IP67, 3000K

Article nr.: PHF725

Flexible LED Leiste vergossen in UV-, Chlor-, Salzwasser- und Lösungsmittelbeständigem weiß/transparenten PVC · für die Innen und Außenanwendung, IP67 · · alle 166,67 mm / 6 LEDs teilbar · Anzahl der LED: 1080 · LED Abstand: 27,78 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro Meter: 479 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 6 W · Lebensdauer L70: >= 36.000 h · LxBxH in mm: 30.000 x 15,5 x 6 · · Temperaturbereich: -20 bis +55° C · Verarbeitungstemperatur: +10 bis +55° C · Maximale Länge pro Anschluss: 20 Meter · Biegedurchmesser: 50 mm · · Leichte Lötfreie Montage durch Steckverbindungen. · Lieferumfang: 30 Meter Rolle, bereits mit einem Einspeisungsverbinder · an jedem Ende · Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835867252
Housing colour	Weiss
Length	30000.00 mm
Width	15.50 mm
Height	6.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	14370.00 lm
Lightoutput per LED	13.31 lm
Lamp	Inklusive LED





VARDAflex Outdoor - 30-Meter-Rolle
Flex. LED-Strip, 24V, 6W/m, IP67, 3000K
Article nr.: PHF725

TECHNICAL DATA

IP rating	67
Power	180 W
Current mA	7500 mA
Voltage	24 V
Amount of LED	1080
Material	Kunststoff
Temperature range	-20 - 55
LED per meter	36
Dimension of segments	166.67 mm
CRI	≥ 80
Lifetime L70B50	36.000 h

