




**VARDAflex Superior IP67 - 5-Meter-
Rolle Flex. LED-Strip, 24V, 4, 8W/m,
IP67, 4000K CRI98**

Article nr.: PGI528

flexible LED Strip · for indoor and outdoor use, IP67 · not UV-resistant · Can be separated every 100 mm or 6 LEDs · Number of LEDs: 300 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >98 · Lumen per metre: 414 lm · Voltage: 24 V DC · Power per meter: 4.8 W · Lifetime L70B50: >= 50.000 h · Energy efficiency class: G · LxWxH in mm: 5.000 x 10 x 4.6 · Easy installation with solderless connector (optional). · Maximum length per connection: 10 metre. New connectors for greater length. · Delivery contents: 5 metre reel with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835895286
Length	5000.00 mm
Width	10.00 mm
Height	4.60 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2070.00 lm
Lightoutput per LED	6.90 lm
Lamp	Inklusive LED
IP rating	67





**VARDAflex Superior IP67 - 5-Meter-
Rolle Flex. LED-Strip, 24V, 4, 8W/m,
IP67, 4000K CRI98**

Article nr.: PGI528

TECHNICAL DATA

Power	24 W
Current mA	1.000 mA
Voltage	24 V
Amount of LED	300
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 98
Lifetime L70B50	50.000 h

