




VARDAflex Neon SVQ S? Flex. LED-Strip, 24V, 12W/m, 3000K

Article nr.: SPHF165

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solventresistant white PVC · for indoor- and outdoor use, IP67/68 · Cuttable every 55.56 mm / 6 LEDs · Amount of LEDs per meter: 108 · LED pitch: 9.26 mm · Beam angle: 160° · CRI: >80 · Luminous flux per meter: 450 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · WxH in mm: 16 x 17 · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 10 meter · Bending radius: 300 mm · anti-wicking ferrule diameter = 12 mm: the anti-wicking ferrule is located at · 115 mm from the connector on the cable.

TECHNICAL DATA

Unit Code	metre
BAR code	4251835861656
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per LED	4.17 lm
Lamp	Inklusive LED
IP rating	68
Voltage	24 V






VARDAflex Neon SVQ S?-?? Flex. LED-Strip, 24V, 12W/m, 3000K

Article nr.: SPHF165

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	108
Dimension of segments	55.56 mm
CRI	≥ 80









VARDAflex Neon SVQ S?-?? Flex. LED-Strip, 24V, 12W/m, 3000K

Article nr.: SPHF165

TECHNICAL DRAWING



Wasserstop

Der Wasserstop befindet sich ca. 115 mm entfernt von der Einspeisung des LED Strips auf der Zuleitung.

Anti-wicking ferrule

The anti-wicking ferrule is located at 115 mm from the connector on the cable.