


VARDAflex Neon SVQ blacklight S?-?? Flex. LED-Strip, 24V, 12W/m, 2700K, blacklight

Article nr.: SPHF833

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solventresistant white PVC · for indoor- and outdoor use, IP67/68 · cuttable every 55.56 mm / 7 LEDs · amount of LEDs per meter: 126 · LED pitch: 7.94 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 97 lm · voltage: 24V DC · power per Meter: 12 W · lifespan L70B50: >= 36,000 h · WxH in mm: 16 x 17 · temperature range: - 20 to +45°C · installation temperature: +10 to +45°C · maximum length per connection: 10 meter · bending diameter horizontal: 300 mm · anti-wicking ferrule diameter = 12 mm: the anti-wicking ferrule is located at · 115 mm from the connector on the cable. · this product contains a light source of energy efficiency class E.

TECHNICAL DATA

Unit Code	metre
BAR code	4251835868334
Housing colour	Schwarz
Width	16.00 mm
Height	17.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per LED	0.77 lm
Lamp	Inklusive LED
IP rating	68
Psb	0,00 W




VARDAflex Neon SVQ blacklight S?-?? Flex. LED-Strip, 24V, 12W/m, 2700K, blacklight

Article nr.: SPHF833

TECHNICAL DATA


Voltage	24 V
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	126
Dimension of segments	55.56 mm
CRI	≥ 80
Lifetime L70B50	36.000 h



VARDAflex Neon SVQ blacklight S?-?? Flex. LED-Strip, 24V, 12W/m, 2700K, blacklight

Article nr.: SPHF833

TECHNICAL DRAWING



Wasserstop

Der Wasserstop befindet sich ca. 115 mm entfernt von der Einspeisung des LED Strips auf der Zuleitung.

Anti-wicking ferrule

The anti-wicking ferrule is located at 115 mm from the connector on the cable.