



**IRIMA A Deckenanbauleuchte inkl.
Deckenanschlusd. L1170, B50,
H75mm, 230V, 33W, IP20, 4000K,
CRI80-RAL9006**

Article nr.: PBA104-9006FS-M

Ceiling lamp with opal cover and homogeneous light surface · with optional integrated UGR foil for glare-free light emission · for indoor use, IP20 · housing: aluminum powder coated · housing colour: white aluminum · beam angle: 60° · power: 33 W · light colour: 4000 K · luminous flux: 3.498 lm · CRI: >80 · lifespan L70: >= 36.000 h · operating voltage: 110 - 305 V AC · protection class I · LxWxH in mm: 1.170 x 50.4 x 75.2 · energy efficiency class: A+ · including LED power supply unit, switchable On/Off · 3-pin connection cable led out of the back of the luminaire

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835811040
Housing colour	RAL9006
Length	1170.00 mm
Width	50.40 mm
Height	75.20 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	3498.00 lm
Lamp	Inklusive LED
IP rating	20





**IRIMA A Deckenanbauleuchte inkl.
Deckenanschlusd. L1170, B50,
H75mm, 230V, 33W, IP20, 4000K,
CRI80-RAL9006**

Article nr.: PBA104-9006FS-M

TECHNICAL DATA

Power	33 W
Voltage	110-305 V
Material	Aluminium
Tollerance	3.00
Efficiency	91.50
Temperature range	-20 - 40
CRI	≥ 80





**IRIMA A Deckenanbauleuchte inkl.
Deckenanschlusssd. L1170, B50,
H75mm, 230V, 33W, IP20, 4000K,
CRI80-RAL9006**

Article nr.: PBA104-9006FS-M

TECHNICAL DRAWING

