



IRIMA P Pendelleuchte inklusive

**Baldachin L1170, B50, H75mm, 230V,
33W, IP20, 3000K, CRI80-RAL9006**

Article nr.: PBA113-9006FS-M

Pendant luminaire with opal cover and homogeneous light surface · with optional integrated UGR foil for glare-free light emission · for indoor use, IP20 · housing: aluminum powder coated · housing color: white aluminum · beam angle: 60° · power: 33 W · light colour: 3000 K · luminous flux: 3.354 lm · CRI: >80 · lifespan L70: >= 36.000 h · operating voltage: 110 – 305 V AC · protection class I · (luminaire) LxWxH in mm: 1.170 x 50.4 x 75.2 · (canopy) LxWxH in mm: 540 x 38 x 50.4 · energy efficiency class: A+ · including LED power supply unit, switchable On/Off · wire suspension 2.000 mm, flexible shortenable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835811132
Housing colour	RAL9006
Length	1170.00 mm
Width	50.40 mm
Height	75.20 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	3354.00 lm
Lamp	Inklusive LED
IP rating	20






IRIMA P Pendelleuchte inklusive

**Baldachin L1170, B50, H75mm, 230V,
33W, IP20, 3000K, CRI80-RAL9006**

Article nr.: PBA113-9006FS-M

TECHNICAL DATA

Power	33 W
Voltage	110-305 V
Material	Aluminium
Tolerance	3.00
Efficiency	91.50
Temperature range	-20 - 40
CRI	≥ 80



Equiv.
SELV



**AKTIV
PFC**



IRIMA P Pendelleuchte inklusive
Baldachin L1170, B50, H75mm, 230V,
33W, IP20, 3000K, CRI80-RAL9006
 Article nr.: PBA113-9006FS-M

TECHNICAL DRAWING

