



**RINDA Pendelleuchte inklusive
Baldachin L1200, Ø60mm, 230V, 27,
4W, IP20, 3000K, CRI80-ALU**

Article nr.: PFE225

Pendant luminaire made of anodized aluminum and opal cover for a homogeneous · light emission. Extremely wide beam for beautiful illumination · for indoor use, IP20 · · housing: aluminum anodized · housing colour: aluminum · beam angle: 270° · power: 27.4 W · light colour: 3000 K · luminous flux: 1.806 lm · CRI: >80 · lifespan L70: >= 36.000 h · operating voltage: 100 - 240 V AC · protection class I · · (luminaire) LxD in mm: 1.200 x 60 · (canopy) LxWxH in mm: 540 x 38 x 50.4 · including LED power supply unit, switchable On/Off · wire suspension 2.000 mm, flexible shortenable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835852258
Housing colour	Aluminium
Length	1200.00 mm
Outer diameter	60 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1806.00 lm
Lamp	Inklusive LED
IP rating	20
Power	27,4 W





**RINDA Pendelleuchte inklusive
Baldachin L1200, Ø60mm, 230V, 27,
4W, IP20, 3000K, CRI80-ALU**
Article nr.: PFE225

TECHNICAL DATA

Voltage	100-240 V
Lamp base	ohne
Material	Aluminium
Tolerance	5.00
Efficiency	86.00
Temperature range	-20 - 40
CRI	≥ 80





**RINDA Pendelleuchte inklusive
Baldachin L1200, Ø60mm, 230V, 27,
4W, IP20, 3000K, CRI80-ALU**
Article nr.: PFE225

TECHNICAL DRAWING

