




CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 3000K, CRI90, D80mm-40°

Article nr.: PEG120

LED power module 31 W with reflector · with Luminus-CXM-14 Power LED Array 4th gen. · for recessed spotlights of the CORU-80(K) product family · input current: 900 mA DC · power: 31 W · luminous flux: 3.347 lm · light colour: 3000 K · CRI: >90 · lifespan L70: >= 50.000 h · beam angle: 40° · protection class III · Excellent heat dissipation due to optimised aluminium heatsink · Aluminium reflector with halogen appearance and uniform light distribution · With 500 mm connection cable and JST plug connection for reverse polarity · protected and tool free replacement of the lamp · inclusive switchable constant current converter · input voltage: 220-240 V AC, 50/60 Hz · protection class II

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835851206
Housing colour	Grau
Height	103.00 mm
Outer diameter	85 mm
Hole size	80 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	3347.00 lm
Lamp	Inklusive LED
IP rating	40






CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 3000K, CRI90, D80mm-40°
Article nr.: PEG120

TECHNICAL DATA

Power	31 W
Current mA	900 mA
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 35
CRI	≥ 90
Lifetime L70B50	50.000 h





CORU-80 LED POWER MODUL CORU-80, 900mA, 31W, 3000K, CRI90, D80mm-40°

Article nr.: PEG120

TECHNICAL DRAWING

