



AULE-515 Ringleuchte DALI - Baldachin
Ø515, H53mm, 230V, 37, 5W, IP20,
3000K, CRI80-RAL9010
 Article nr.: PBE007-9010

Round pendant luminaire with light emission to the outside and downwards · for indoor use, IP20 · including canopy with max. 3.000 mm rope suspension · housing: aluminum powder coated · colour of housing: RAL 9010 (pure white) · beam angle: 96° · power: 37.5 W · light colour: 3000 K · luminous flux: 2.617 lm · CRI: >80 · lifespan L70: >= 36.000 h · input voltage: 100-240 V AC, 50/60 Hz · protection class I · height: 53 mm · outer diameter: 515 mm · including power supply, DALI dimmable · tool-free locking mechanism for quick assembly

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835825078
Housing colour	Weiss
Height	53.00 mm
Outer diameter	515 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	2617.00 lm
Lamp	Inklusive LED
IP rating	20
Power	37,5 W



**Ø515, H53mm, 230V, 37, 5W, IP20,
3000K, CRI80-RAL9010**



AULE-515 Ringleuchte DALI - Baldachin
Ø515, H53mm, 230V, 37, 5W, IP20,
3000K, CRI80-RAL9010
 Article nr.: PBE007-9010

TECHNICAL DRAWING

