



AULE-515 Ringleuchte CASAMBI -

Baldachin Ø515, H53mm, 230V, 37, 5W,
IP20, 3000K, CRI80-RAL9006

Article nr.: PBE008-9006

Round pendant luminaire with light emission to the outside and downwards · for indoor use, IP20 · including canopy with max. 3.000 mm rope suspension · housing: aluminum powder coated · colour of housing: RAL 9006 (white aluminum matt) · beam angle: 96° · power: 37.5 W · light colour: 3000 K · luminous flux: 2.617 lm · CRI: >80 · lifespan L70: >= 36.000 h · input voltage: 100-240 V AC, 50/60 Hz · protection class I · height: 53 mm · outer diameter: 515 mm · including power supply, CASAMBI dimmable · tool-free locking mechanism for quick assembly

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835825320
Housing colour	RAL9006
Height	53.00 mm
Outer diameter	515 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	2617.00 lm
Lamp	Inklusive LED
IP rating	20
Power	37,5 W





AULE-515 Ringleuchte CASAMBI -

Baldachin Ø515, H53mm, 230V, 37, 5W,
IP20, 3000K, CRI80-RAL9006

Article nr.: PBE008-9006

TECHNICAL DATA

Voltage	100-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	to 45
CRI	≥ 80





AULE-515 Ringleuchte CASAMBI -

Baldachin Ø515, H53mm, 230V, 37, 5W,
IP20, 3000K, CRI80-RAL9006

Article nr.: PBE008-9006

TECHNICAL DRAWING

