



AULE-1025 Ringleuchte DALI -
Baldachin Ø1025, H53mm, 230V, 83,
6W, IP20, 3000K, CRI80-RAL9010
 Article nr.: PBE011-9010

Round pendant luminaire with light emission to the outside and downwards · for indoor use, IP20 · including canopy with max. 3.000 mm rope suspension · housing: aluminum powder coated · colour of housing: RAL 9010 (pure white) · beam angle: 96° · power: 83.6 W · light colour: 3000 K · luminous flux: 5.838 lm · CRI: >80 · lifespan L70: >= 36.000 h · input voltage: 100-240 V AC, 50/60 Hz · protection class I · height: 53 mm · outer diameter: 1.025 mm · including power supply, DALI dimmable · tool-free locking mechanism for quick assembly

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835825115
Housing colour	Weiss
Height	53.00 mm
Outer diameter	1025 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	5838.00 lm
Lamp	Inklusive LED
IP rating	20
Power	83,6 W





AULE-1025 Ringleuchte DALI -
Baldachin Ø1025, H53mm, 230V, 83,
6W, IP20, 3000K, CRI80-RAL9010
 Article nr.: PBE011-9010

TECHNICAL DATA

Voltage	100-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	to 45
CRI	≥ 80





AULE-1025 Ringleuchte DALI -
Baldachin Ø1025, H53mm, 230V, 83,
6W, IP20, 3000K, CRI80-RAL9010
 Article nr.: PBE011-9010

TECHNICAL DRAWING

