



**AULE-740 Ringleuchte CASAMBI Ø740,
H53mm, 230V, 57, 6W, IP20, 3000K,
CRI80-RAL9006**

Article nr.: PBE030-9006

Round pendant luminaire with light emission to the outside and downwards · for indoor use, IP20 · with max. 3.000 mm rope suspension · housing: aluminum powder coated · colour of housing: RAL 9006 (white aluminum matt) · beam angle: 96° · power: 57.6 W · light colour: 3000 K · luminous flux: 4.026 lm · CRI: >80 · lifespan L70: >= 36.000 h · input voltage: 100-240 V AC, 50/60 Hz · protection class I · height: 53 mm · outer diameter: 740 mm · including power supply, CASAMBI dimmable · tool-free locking mechanism for quick assembly

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835825467
Housing colour	RAL9006
Height	53.00 mm
Outer diameter	740 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4026.00 lm
Lamp	Inklusive LED
IP rating	20
Power	57,6 W





**AULE-740 Ringleuchte CASAMBI Ø740,
H53mm, 230V, 57, 6W, IP20, 3000K,
CRI80-RAL9006**

Article nr.: PBE030-9006

TECHNICAL DATA

Voltage	100-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	to 45
CRI	≥ 80





**AULE-740 Ringleuchte CASAMBI Ø740,
H53mm, 230V, 57, 6W, IP20, 3000K,
CRI80-RAL9006**
Article nr.: PBE030-9006

TECHNICAL DRAWING

