



CORMA-770 Ringleuchte DALI -
Baldachin Ø770, H53mm, 230V, 69, 2W,
IP20, 3000K, CRI80-RAL9006
 Article nr.: PBE003-9006

Round pendant luminaire with light emission inwards and downwards · for indoor use, IP20 · including canopy with max. 3.000 mm rope suspension · housing: aluminum powder coated · colour of housing: RAL 9006 (white aluminum matt) · beam angle: 96° · power: 69.2 W · light colour: 3000 K · luminous flux: 6.909 lm · CRI: >80 · lifespan L70: >= 36.000 h · input voltage: 100-240 V AC, 50/60 Hz · protection class I · height: 53 mm · outer diameter: 770 mm · including power supply, DALI dimmable · tool-free locking mechanism for quick assembly

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835825276
Housing colour	RAL9006
Height	53.00 mm
Outer diameter	770 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	6909.00 lm
Lamp	Inklusive LED
IP rating	20
Power	69,2 W





CORMA-770 Ringleuchte DALI -

**Baldachin Ø770, H53mm, 230V, 69, 2W,
IP20, 3000K, CRI80-RAL9006**

Article nr.: PBE003-9006

TECHNICAL DATA

Voltage	100-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	to 45
CRI	≥ 80





CORMA-770 Ringleuchte DALI -
Baldachin Ø770, H53mm, 230V, 69, 2W,
IP20, 3000K, CRI80-RAL9006
 Article nr.: PBE003-9006

TECHNICAL DRAWING

