



VARDAflex Plus DTW - 5-Meter-Rolle


Flex. LED-Strip, 24V, 7, 5W/m, Innen, DTW CRI80

Article nr.: PGI141

flexible LED Strip with self adhesive backside, · for indoor use. · · can be separated every 100 mm or 12 LEDs · number of LEDs: 600 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · lumen per meter: 772 lm · Light colour: 3300 K - 1900 K (Dim To Warm) · voltage: 24 V DC · power per meter: 7.5 W · lifetime L70B50: >=50.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 10 x 1,5 · · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll with 300 mm connecting cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835891417
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	3300-1900K Dim to Warm
Lightoutput per fixture	3860.00 lm
Lightoutput per LED	6.43 lm
Lamp	Inklusive LED






VARDAflex Plus DTW - 5-Meter-Rolle

Flex. LED-Strip, 24V, 7, 5W/m, Innen, DTW CRI80

Article nr.: PGI141

TECHNICAL DATA

IP rating	20
Power	37,5 W
Current mA	1.563 mA
Voltage	24 V
Amount of LED	600
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h





VARDAflex Plus DTW - 5-Meter-Rolle
Flex. LED-Strip, 24V, 7, 5W/m, Innen,
DTW CRI80

Article nr.: PGI141

TECHNICAL DRAWING

