




VARDAflex Premium Green Double-7-M.-Rolle Flex. LED-Strip, 24V, Innen, 2700K CRI90

Article nr.: PGB497

flexible LED Strip with self adhesive backside, · for indoor use. · · can be separated every 83.33 mm or 7 LEDs · number of LEDs: 588 · LED pitch: 11.9 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 2400 lm · voltage: 24V DC · power per meter: 20 W · lifespan L70B50: >= 60,000 h · lifespan L80: >= 60,000 h · lifespan L90B20: > 50,000 h · energy efficiency class: E · LxWxH in mm: 7,000 x 10 x 1.3 · · Easy installation with solderless connector (optional). · Maximum length per connection: 7 meter. New connectors for greater length. · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Delivery contents: 7 meter roll with 300 mm connecting cable · rutec recommends the usage of a dimming actuator between power supply and · LED strip. · Eligible for funding under the BEG funding programme 2021 - 2030

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835824972
Length	7000.00 mm
Width	10.00 mm
Height	1.30 mm
LED colour	ca. 2700 K ultra warmweiß
Lightoutput per fixture	16800.00 lm
Lightoutput per LED	28.57 lm
Lamp	Inklusive LED
IP rating	20






VARDAflex Premium Green Double-7-M.-Rolle Flex. LED-Strip, 24V, Innen, 2700K CRI90

Article nr.: PGB497

TECHNICAL DATA

Power	140 W
Psb	0,00 W
Current mA	5.833 mA
Voltage	24 V
Amount of LED	588
Temperature range	-20 - 85
LED per meter	84
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	60.000 h





**VARDAflex Premium Green Double-7-
M.-Rolle Flex. LED-Strip, 24V, Innen,
2700K CRI90**

Article nr.: PGB497

TECHNICAL DRAWING

