




VARDAflex Premium Green Double-7-M.-Rolle Flex. LED-Strip, 24V, Innen, 4000K CRI90

Article nr.: PGB498

flexible LED Strip with self adhesive backside, · for indoor use. · · can be separated every 83.33 mm or 7 LEDs · number of LEDs: 588 · LED pitch: 11.9 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 2704 lm · voltage: 24V DC · power per meter: 20 W · lifespan L70B50: >= 60,000 h · lifespan L80: >= 60,000 h · lifespan L90B20: > 50,000 h · energy efficiency class: D · LxWxH in mm: 7,000 x 10 x 1.3 · · Easy installation with solderless connector (optional). · Maximum length per connection: 7 meter. New connectors for greater length. · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Delivery contents: 7 meter roll with 300 mm connecting cable · rutec recommends the usage of a dimming actuator between power supply and · LED strip. · Eligible for funding under the BEG funding programme 2021 - 2030

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835824989
Length	7000.00 mm
Width	10.00 mm
Height	1.30 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	18928.00 lm
Lightoutput per LED	32.19 lm
Lamp	Inklusive LED
IP rating	20






VARDAflex Premium Green Double-7-M.-Rolle Flex. LED-Strip, 24V, Innen, 4000K CRI90

Article nr.: PGB498

TECHNICAL DATA

Power	140 W
Psb	0,00 W
Current mA	5.833 mA
Voltage	24 V
Amount of LED	588
Temperature range	-20 - 85
LED per meter	84
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_D
CRI	≥ 90
Lifetime L70B50	60.000 h





**VARDAflex Premium Green Double-7-
M.-Rolle Flex. LED-Strip, 24V, Innen,
4000K CRI90**

Article nr.: PGB498

TECHNICAL DRAWING

