




VARDAflex Quantum Ultra-V2 - 5-Meter-Rolle Flex. LED-Strip, 24V, Innen, 3000K CRI80

Article nr.: PHA125

flexible LED Strip with self adhesive backside, · for indoor use. · can be separated every 66.67 mm or 8 LEDs · number of LEDs: 600 · LED pitch: 8.33 mm · beam angle: 120° · CRI: >80 · lumen per meter: 3326 lm · voltage: 24 V DC · power per meter: 21.5 W · lifetime L70B50: >= 67.000 h · energy efficiency class: D · LxWxH in mm: 5.000 x 10 x 2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 metre. New connectors for greater length. · Delivery contents: 5 metre reel with 150 mm connecting cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835811255
Housing colour	ohne
Length	5000.00 mm
Width	10.00 mm
Height	2.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	16630.00 lm
Lightoutput per LED	27.71 lm
Lamp	Inklusive LED






VARDAflex Quantum Ultra-V2 - 5-Meter-Rolle Flex. LED-Strip, 24V, Innen, 3000K CRI80

Article nr.: PHA125

TECHNICAL DATA

IP rating	20
Power	107,5 W
Current mA	4.479 mA
Voltage	24 V
Amount of LED	600
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	66.67 mm
Energy efficiency class	EEK-Label_D
CRI	≥ 80
Lifetime L70B50	67.000 h





VARDAflex Quantum Ultra-V2 - 5-Meter-Rolle Flex. LED-Strip, 24V, Innen, 3000K CRI80

Article nr.: PHA125

TECHNICAL DRAWING

