



Kontstantstrom Konverter Dimmbar LED Konverter 600mA 4, 8W-7, 2W

Article nr.: PHE955

rutec LED constant current converters dimmable · for indoor use · Built-in active power factor correction (active PFC) · IP64 · Protection Class 2, CE, RoHS, REACH · Protection against short-circuit and overload · Primary and secondary-sided 1 supply and feed line · Dimmable with phase cut dimmers · (Tronic dimmer) e.g. Berker 286710

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835859554
Housing colour	Weiss
Height	27.00 mm
Outer diameter	66 mm
Lamp	Ohne
IP rating	64
Power	4,8-7,2 W
Psb	0,00 W
Pno	2,30 W





Kontstantstrom Konverter Dimmbar
LED Konverter 600mA 4, 8W-7, 2W
Article nr.: PHE955

TECHNICAL DATA

Current mA	600 mA
Input voltage	230
Output voltage	8-12
Material	Kunststoff
Tolerance	6.00
Temperature range	-20 - 50
Suitable light source	LED





Kontstantstrom Konverter Dimmbar
LED Konverter 600mA 4, 8W-7, 2W
 Article nr.: PHE955

TECHNICAL DRAWING

