

DALI Touchpanel Glas - schwarz AC-DALI Touchpanel 4 ZONEN RGBW

Article nr.: PHZ530

DALI touch panel, 4 zones RGBW, including power supply for 230 V AC connection · for indoor use · Material: plastic, glass · IP20 · Protection class II, CE, RoHS · Voltage: 100 - 230 V AC, 50 Hz · Standby power: 1,5 W · Transmission power: max. 4 W · Signal: DALI · Device Type: DT6 · Maximum cable cross-section at terminal: 1.5 sq mm · DALI start address manually adjustable via 2 potentiometer · per zone: address management of 4 addresses possible · in acc. w. DALI standard protocol IEC 62386-102, IC 62386-207 · suitable for standard DALI devices · Dimmer range 0.1 - 100 % · Control up to 4 zones independently · highly sensitive touch colour wheel · quick, precise colour control · Selection of 10 different preprogrammed colour gradients · dimming and switching of single and mixed colors · per zone: 4 memory functions for colour scene or - sequence · several DALI touch panels per DALI bus line possible

TECHNICAL DATA

Unit Code	pcs
BAR code	4251835805308
Housing colour	Schwarz
Length	86.00 mm
Width	86.00 mm
Height	42.00 mm
Hole size	55 mm
Depth in ceiling	50.00 mm
Lamp	Ohne
IP rating	20

rutec Projekt GmbH
Tel. +49 4242 / 95 65 750
Carl-Zeiss-Str.15
info@rutecprojekt.de
28857 Syke
www.rutecprojekt.de



DALI Touchpanel Glas - schwarz AC-DALI Touchpanel 4 ZONEN RGBW

Article nr.: PHZ530

TECHNICAL DATA

Power	2 W
Input voltage	100-240
Material	Glas
Temperature range	-20 - 50

rutec Projekt GmbH
Tel. +49 4242 / 95 65 750

Carl-Zeiss-Str.15
info@rutecprojekt.de

28857 Syke
www.rutecprojekt.de



DALI Touchpanel Glas - schwarz AC-DALI Touchpanel 4 ZONEN RGBW


Article nr.: PHZ530


TECHNICAL DRAWING

rutec Projekt GmbH
Tel. +49 4242 / 95 65 750

Carl-Zeiss-Str.15
info@rutecprojekt.de

28857 Syke
www.rutecprojekt.de


86
60
60
86


32
42